

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claim 1 (currently amended): A rotary engine, comprising:

a spherical combustion chamber having an internal groove;  
a rotor extending into the spherical combustion chamber;  
a first baffle having a ridge in engagement with the  
internal groove; and

a second baffle supported by the rotor;  
wherein the second baffle has a circular face and a longitudinal  
groove therein, and the first baffle has one edge in engagement  
with the longitudinal groove in the second baffle, whereby the  
first baffle prevents rotation of the second baffle about an axis  
of the rotor.

Claim 2 (original): A rotary engine according to Claim 1,  
wherein ~~the second baffle has a circular face, and~~ the first  
baffle has a semicircular face.

Claim 3 (canceled)

Claim 4 (currently amended): A rotary engine according to Claim 1, wherein ~~the second baffle has a circular face, and~~ the first baffle has a semicircular face; and wherein the rotor comprises a rod and a slanted annular face in sliding engagement with the second baffle;

whereby the second baffle oscillates during rotation of the rotor.

Claim 5 (currently amended) A rotary engine according to Claim 1, wherein ~~the second baffle has a circular face and a longitudinal groove therein, and the first baffle has one edge in engagement with the longitudinal groove in the second baffle,~~ whereby the first baffle oscillates in a side to side movement along the groove in the spherical combustion chamber during rotation of the rotor.

Claim 6 (currently amended): A rotary engine, comprising:

a spherical combustion chamber;

a rotor extending into the combustion chamber;

a first baffle;

a second baffle;

guiding means for guiding the first baffle in an oscillatory motion with the combustion chamber;

connecting means for connecting the second baffle to the rotor such that rotation of the rotor causes oscillatory movement of the second baffle;

wherein the second baffle has a circular face and a longitudinal groove therein, and the first baffle has one edge in engagement with the longitudinal groove in the second baffle, whereby the first baffle prevents rotation of the second baffle about an axis of the rotor.

Claim 7 (currently amended): A rotary engine according to Claim 6, wherein ~~the second baffle has a circular face, and~~ the first baffle has a semicircular face.

Claim 8 (canceled)

Claim 9 (original): A rotary engine according to Claim 6, further comprising a cam sleeve operated by rotation of the rotor.

Claim 10 (currently amended): A rotary engine, comprising:  
a spherical combustion chamber;  
a rotor extending into the combustion chamber;  
a first baffle;  
a second baffle;  
guiding means for guiding the first baffle in an oscillatory motion with the combustion chamber;  
connecting means for connecting the second baffle to the rotor such that rotation of the rotor causes oscillatory movement of the second baffle; and

~~according to Claim 6, further comprising~~ lifting rods mounted on an external surface of the spherical combustion chamber.

Claim 11 (original): A rotary engine according to Claim 6, further comprising a cam sleeve operated by rotation of the rotor, and lifting rods mounted on an external surface of the spherical combustion chamber.